(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 19 May 2005 (19.05.2005)

PCT

(10) International Publication Number WO 2005/045251 A1

(51) International Patent Classification7:

F04D 17/12

(21) International Application Number:

PCT/EP2004/012488

(22) International Filing Date:

1 November 2004 (01.11.2004)

(25) Filing Language:

English

(26) Publication Language:

English


(30) Priority Data: MI2003A002149 7 November 2003 (07.11.2003)

- (71) Applicant (for all designated States except US): NUOVO PIGNONE HOLDING S.P.A. [IT/IT]; Via F. Matteucci, 2, I-50127 Firenze (IT).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): SARRI, Franco [IT/IT]; Via Burchietti, 29, I-50018 Scandicci (IT).

- (74) Agents: COPPO, Alessandro et al.; Ing. Barzano' & Zanardo Milano S.p.A., Via Borgonuovo, 10, I-20121 Milano (IT).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE,

[Continued on next page]

(54) Title: MULTISTAGE CENTRIFUGAL COMPRESSOR AND METHOD FOR ASSEMBLY THE SAME



(57) Abstract: Multistage centrifugal compressor having a tank which can be opened horizontally, comprising a lower semi-tank (11) and an upper semi-tank (12), a shaft 13 having a series of rotors 14 and a series of stages (10) each of which comprising, in turn, a series of lower semi-diaphragms 16 and a series of upper semi-diaphragms 18, a lower halfring (21) and an upper half-ring (22) which can be coupled to form a bearing ring, the lower half-ring (21) being fastened internally to the lower semi-tank (11), and the corresponding upper half-ring (22) being fastened to the upper semi-tank (12), in each stage (10) of the multistage centrifugal compressor, the lower semi-diaphragms 16 are rigidly constrained to one another by blocking means, to form a first pile (41) of lower semi-diaphragms (16) and, the corresponding upper semi-diaphragms (18) are rigidly constrained to one another by blocking means, to form a second pile (42) of lower semi-diaphragms (16), the first pile (41) can be constrained to the lower half-ring (21) and the second pile (42) can be constrained to the upper half-ring (22).

WO 2005/045251 A1



SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

with international search report